Data Sheet



Coaxial Panel Connector 23_N-50-0-23/133_N

Description

Straight panel receptacle jack, flange mount

Interface standards
IEC 61169-16_MIL-STD-348A/304_CECC 22210



Technical Data

Electrical Data

Impedance 50 Ω Interface frequency max. 11 GHz

Mechanical Data

Number of matings 500
Weight 0.0242 kg

Environmental Data

Operating temperature -65 °C to 165 °C 2011/65/EU (RoHS) compliant

Material Data

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	

Related Documents

Outline drawing DOU-00010601
Catalogue drawing DCA-00010603

Ordering Information

Single package 23_N-50-0-23/133_NE

HUBER+SUHNER is certified according to ISO 9001, ISO 14001, ISO/TS 16949 and IRIS

www.hubersuhner.com

Waiver: It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general information purposes only.