

COAXIAL CONNECTOR, SMA-26.5GHz, 50 Ohm, Straight panel receptacle, jack (female), flange mount

23_SMA-50-0-94/199_N

Properties

- Excellent return loss
- Intermateable with PC3.5 and SK
- Applicable in frequencies up to 18 GHz



Product configuration		
Interface type	Gender	Standard
SMA	jack	HUBER+SUHNER-SMA-26.5GHz
Interface and material data		
Piece parts	Material	Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer conductor	Stainless Steel	
Body	Stainless Steel	
Insulator	PFA / PTFE	
Electrical data		
Impedance	50 Ω	
Interface frequency	26.5 GHz	
Mechanical data		
Weight	0.0029 kg	
Mating cycles	500	
Flange type	square flange / others	
Tab style	Stripline	
Environmental data		
Operation temperature	-65 °C ... 125°C	
Ordering Information Table		
Item number	Item description	Packaging type
22649049	23_SMA-50-0-94/199_NE	Single

COAXIAL CONNECTOR, SMA-26.5GHz, 50 Ohm, Straight panel receptacle, jack (female), flange mount

23_SMA-50-0-94/199_N

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.
DOCUMENT PIM-P2691 / Date of publication: 26.11.2023 / uncontrolled copy