

DRAWING



MOUNTING HOLE



3	1	Body	Brass/Gold plated	
2	1	Insulator	PTFE	
1	1	Center contact	Beryllium copper/Gold plated	

Designed by	Checked by	Approved by	Date	File name	Scale
Xio Xang	Jing Lo	Jing Chan	26.02.09	SMA_SMA-2214(24.3)	1 : 1

RF CONNEC
excellent way of connect

SMA_SMA-2214(24.3)

Edition	Sheet
1.0	1/1

CHARACTERISTICS

DESCRIPTION:	ADAPTOR SMA JACK TO SMA JACK FL

Electrical data:

Impedance:	*50 ohm*
Frequency range:	*DC to 18.0 GHz*
VSWR:	*≤1.03 + 0.02 X f [GHz]*
Insertion loss:	*≤0.10 X $\sqrt{f[GHz]}$ dB*
Insulation resistance:	*≥5000MΩ*
Test voltage:	*1000 V rms*
Working voltage:	*480 V rms*
Contact resistance:	
1). Centre contact:	*3.0 mΩ*
2). Outer conductor:	*2.0 mΩ*

Environmental data:

Temperature rating:	*-65 ° C to +165 ° C*
2002/95/EC (RoHS):	*Compliant*

Mechanical data:

Mating cycles:	*≥500*
Center contact captivation:	*≥15 N(axial)*
Recommended torque:	*0.46Nm to 0.69Nm*

Suitable cables:

N/A